




DSC ALL STAINLESS STEEL BALANCED PRESSURE THERMOSTATIC STEAM TRAP WITH UNIVERSAL CONNECTOR

No.S79 · S79F

MOP 32K x 320°C




- DSC S79 ALL STAINLESS STEEL BALANCED PRESSURE THERMOSTATIC STEAM TRAP WITH UNIVERSAL CONNECTOR. THERMOSTATIC WELDED UNIT CAN BE REPLACED WITHOUT DISTRIBUTING PIPE .
- EXCELLENT CORROSION RESISTANCE.
- EXCELLENT RESISTANCE TO HYDRAULIC SHOCKS.
- NOT VENT AIR AND CO₂ AT STEAM TEMPERATURE.
- GOOD OPERATION AGAINST BACK PRESSURE.
- GOOD RESISTANCE TO DAMAGE FROM FREEZING.
- DELAYED RESPONSIVENESS TO SLUGS OF CONDENSATE.
- ONE YEAR SATISFACTORY SERVICE GUARANTEED.
- INTERNAL CHECK VALVE OPTIONAL.



No.S79/C2 DIMENSIONS(MM). MOP(KG/CM²). WT(KG)

No.	CONN.SE*	A	B	C	MOP	WT.
S79/C2	15	72	68	55	32	0.9
	20	72	68	55	32	0.9
	25	76	74	60	32	1.2

* NPT. BSPT. SE AVAILABLE.



No. S79/C2F

No.	CONN.FE*	FF	B	C	MOP	WT.
S79/C2F	15	150	68	55	32	2.6
	20	150	68	55	32	3.1
	25	160	74	60	32	3.8

* DIN FLANGE STANDARD. OTHER SPEC. CONSULT FACTORY.

S79 CONSTRUCTION OF MATERIALS

BODY	S.S.304
SEAT	S.S.420 HARDEND
SEAT GASKET	S.S.316
CAGE UNIT	S.S.304
DIAPHRAGM	MIXED CEMICAL
STRAINER	S.S.304
CHECK VALVE	S.S.420

C2 CONSTRUCTION OF MATERIALS

BODY	CF8
STRAINER	S.S.420 HARDEND
STRAINER GASKET	S.S.304
STRAINER CAP	S.S.304
FLANGE	S.S.304
BLOTS	CARBON STEEL

CONDENSATE DISCHARGE CAPACITY IN KG/HR

